

AMERICAN WOOD OIL PREMIUM WOODCARE













A GLANCE AT

Discover our commitment to the environment and our company history. As well as new projects and products.

Our commitment 06
Our history
New website
New products
New projects

INTERIOR

We understand the needs and the wishes of our designers, architects, builders, installers and end-consumers.

We have developed a full range of products, offering solutions for interior applications.

Introduction	02-03
Aging Powder	07
Fix and Tone	
Transparent Gold	08-09
Warm Grey	10-11
SuperGreen+	12-13
Color Pigments	14
NYC Colors	15
Clear Seal Oil	16-17
HardWax Oil	18-19
4Nature	20-21
Application	22
Maintenance	23

EXTERIOR

To protect the natural beauty of the exterior wood applications, we proudly present our premium products.

We have developed a full range of products, offering solutions for exterior applications.

Introduction	24-25
Crystal Cleaner	26-27
California	28-29

INDUSTRY


Over the last several years, more and more manufacturers are enjoying the benefits of our finishes.

These benefits include endless options of color possibilities and superior stain protection. Watermarks and household stains (such as ketchup, wine, ...) are a thing of the past, due to the natural water repellency of our finishes.

The viscosity and flexibility of our finishes allow for shorter oxidized drying times during the prefinishing process.

Shorter dry times mean more coats in less time, speeding up the manufacturing process!

Factory Finishing 30-31



CREATIVITY EQUALS SOLUTIONS

4 American Wood Oil 5

OUR COMMITMENT

We are committed to the environment! In today's eco-conscious society we're all doing a little more to try to make a difference in the World around us. Our traditional way of making floor and wood finishes are adapted to the new nature friendly standards. We still use natural oils like Tung Oil, Brazilian Rosewood Oil and Linseed Oil. Carefully gathered, pressed and purified, this creates a natural base for our wood finishes since decades

Thanks to the use of those natural oils, a completely natural and renewable resource, we literally lock out water with formulas who relies on the protective nature of resins and the penetrating sealing advantages of our special blends. The Legendary American Wood Oil permeates wood surfaces and actually becomes part of the wood itself to resist household stains and moisture.

The Legendary American Wood Oil comes in different formulas designed to work for the specific needs of each different small or large project, interior or exterior.

We are committed to partners, suppliers and our independent distributors and dealers. We say "no" to big DIY-stores and sell only to independent distributor and dealers. In doing so, we support the local professional to build together with him in his market an strong share We are proof that the quality ingredients and manufacturing methods can also be Earth friendly. This commitment is the most important part of our product mix!

OUR HISTORY

The original Tung Oil Finish has been made by the Hawkins family in the USA since 1916 according to the original family formula. Since more than 12 years The Legendary American Wood Oil, using this technology, is global available as a high quality finish for hardwood floors and all

In the 14th century Tung oil has been used to waterproof and protect wooden ships from the eroding powers of the sea. The penetrating finish of the Hawkins original Tung Oil has been the first choice for many wood floor specialists, furniture makers, antique restorers for over a 100

As a result of the global demand for designer colors, the product range has been enlarged with rainbow pigments. For the global demand having different final finishing appearances such as HardWax Oil and Waterbased laquers. We are providing new products to our product program every year, to keep up with new developments and trends. Having the best penetrating drying oil, highly water-resistant that never

Hundreds of professional contractors rely on The Legendary American Wood Oil to provide the best finish in woodcare that their customers can get. We hope to serve them also the next hundreds years to come.

NEWS

NEW WEBSITE

We have produced a new updated website for your convenience.

Please look us up at www.americanwoodoil.com



NEW PRODUCTS

The trend towards reclaimed and aged wood flooring is developing. We are now offering Aging Powder H48. Aging Powder H48 accelerates the aging process on new and refinished wood!

For professionals and manufacturers who prefer our standard color tones, we are now offering the pre-mixed NYC color range in a special 5 litre metal

- Aging powder H48, step 1
- Fix & Tone, aging fixate and stabilizer step 2
- NYC pre-mixed standard

NEW PROJECTS

The Italian embassy in London Benott wood flooring LTD a London based company did an amazing job installing and finishing the wooden floors.

Little Venice in Baku The company Tutto Bello used "California" to finish all the exterior wood, in this incredible high-end project in Baku, Azerbaijan

Wesco

Wesco in the UK is using American Wood Oil in their coloring unit to offer premium pre-finished natural oiled products to their custumers.

Best kept secret

The company V.A Hutchison a wood floor company who's been in business over 25 vears reffered to American Wood Oil as the best kept secret in the wood flooring industry.



AGING POWDER

AGING BY OXIDATION FOR WOODEN FLOORS, FURNITURE, WOOD PANELING, DOORS ETC.

Aging Powder H48 oxidized new and old interior wood.

Formulated as on oxidizing agent, it is mixed with water, applied, and within a few short hours the wood takes on a graying patina and an "aged" appearance. Just as if it was naturally aging for decades!

- · Suitable for oak and all tannic woods
- · Penetrates into the wood
- · Eco-aware, a water based formula
- · Works on new wood or on refinishing projects
- Application by hand or by industrial means
- Alternative for expensive antique or reclaimed wood



FIX & TONE


FIXATING, STABILIZING AND ADAPTING AGING POWDER FOR WOODEN FLOORS, FURNITURE, WOOD PANELING, DOORS ETC.

Fix & Tone is a special blend of natural oil, pigments and waxes. It's used to fixate, stabilize and adapt the interior wood after the oxidizing process of Aging Powder H48. Fix & Tone provides the possibility to retain the light grey tone from the oxidizing process with Stabilizer H48 or to enrich the tone with special colors: Chalk White, Bark Brown or Charcoal Black.

- Unique color tones:
- Stabilizer H48 (retaining the light grey tone)
- · Chalk White
- Bark Brown
- Charcoal Black
- · Fixates and adapts the color tone
- Free flowing and flexible
- Eco-aware, low VOC
- Will not crack, flake, blister or peel
- Special aged appearance



6 American Wood Oil American Wood Oil 7



Transparent Gold is a unique blend of pure Tung oil and resin. Originally formulated to protect all interior woodwork. Still made by hand according to the original formula from the Hawkins family since 1916.

- Suitable for all types of wood
- Exotic woods, soft and hard woods
- Penetrates naturally & deeply into the wood
- Water resistant: when used as a finishing system in multiple coats
- Eco-responsible, made from the natural tung nut and 90% of the resin portion of the formula is from renewable natural resources
- Semi-satin







Transparent Gold on an Oak Floor

WARM GREY


HIGH QUALITY INTERIOR WOOD COLORING AND PROTECTING STAIN

Warm Grey is a unique blend of pure Tung oil, resin and brightening pigment. Originally formulated to protect all interior woodwork. Still made by hand according to the original formula from the Hawkins family since 1916.

- Suitable for dense and hardwood
- Penetrates naturally and deeply into the wood
- Micro-porous, fills pores
- Used as a basic coat, ensures the wood does not amber
- Warm natural appearance, free from added sheen and color
- Will not crack, flake, blister or peel
- Natural "unfinished " appearance
- Mat
- Finish with Clear Seal, HardWax oil or 4Nature



Warm Grey on an Oak Floor





SuperGreen+ is an ecological blend of pure Tung oil, Brazilian Rosewood Oil and all natural vegetable and soy resins.

The result is a ZERO VOC, new age oil, manufactured to the highest environmental standards. Completely safe for use around children and pets.

- Suitable for all types of wood
- No Odor
- Penetrates naturally and deeply into the wood
- Water repellant
- UV resistant
- Color pigments can be added
- Eco and Environmentally friendly
- ZERO VOC
- Semi-satin/matt finish
- Can be finished with HardWax oil



California, USA



SuperGreen+ on bamboo floor

SUPERGREEN+

HIGH QUALITY TUNG AND ROSEWOOD OIL

12 American Wood Oil American Wood Oil

COLOR PIGMENTS

CREATE YOUR OWN UNIQUE COLORS



A specially formulated pallet of 10 color pigments are available to blend with our Transparent Gold, Warm Grey, SuperGreen+ and HardWax oils.

- White
- Grey
- Olive Grey
- Boston Grey
- Cherry
- Tile Red
- Mahogany
- Belgium Beige
- Brown
- Black



Our rainbow pasta color pigments allow you to create the desired color you or your designer prefers. We are offering a standard color range with formulations or the possibility to create an endless array of custom colors. Custom colors can be achieved by mixing different color pigments into the preferred oils or HardWax oils.

With a maximum of 4 pigments into one US gallon.

www.americanwoodoil.com



NYC COLORS

PRE-MIXED COLORS

Ready to use, standard color range, pre-mixed in a special metal container.

1 US Gallon (3,875 el covers over 80m²)





MANHATTEN

1 US GALLON Warm Grey



QUEENS

1 US GALLON Warm Grey + 1 Pigment Grey




WHITE PLAINS

1 US GALLON Transparent Gold



HUDSON

1 US GALLON Transparent Gold + 1 Pigments Olive Grey



BERGEN

1 US GALLON Transparent Gold + 1 pigment Cherry



RICHMOND

1 US GALLON Transparent Gold + 1 Pigment Mahogany




PASSAIC

1 US GALLON Transparent Gold



ROCKLAND

1 US GALLON Warm Grey + 1 Black + 1 Grey



BRONX

1 US GALLON Transparent Gold + 1 Pigment Brown




WESTCHESTER

1 US GALLON Transparent Gold + 3 Pigment Brown



BROOKLYN

1 US GALLON Transparent Gold + 1 Pigment Boston Grey



PUTNAM

d 1 US GALLON Transparent Gold + 3 Pigment Black

14 American Wood Oil
American Wood Oil



HIGH QUALITY TUNG OIL FINISH

Clear Seal is a unique Tung oil interior wood finish offering excellent water resistance and superior protection against household products such as wine, ketchup, coffee, mustard,.... The NIAGARAH20 formula continues to deliver spectacular results that give the user all the attributes of a traditional natural oil finish with the added durability of our special finishing blends.

It prevents splintering of the wood and also has an excellent slip-retardent proporties. Clear Seal is formulated to fixate and seal off the color accomplished with American Wood Oil.

Clear Seal is compatible with all other natural oils and pre-finished floors that are achieved with oxydised natural oil. It will prevent the absorbation of grease and dirt.

- Suitable for all types of wood, dense, hard and exotic wood
- Penetrates naturally and deeply into the wood
- Fills pores, forms a film inside the wood grain
- Very water repellent
- Extra durable protective finish against household stains
- Clear, translucent, non-coloring finish on top of color
- Can be used on top of unfinished wood, will slightly yellow
- Conform EU Directive 2004/42/CE
- Matt, slight sheen



Clear Seal on top of pre-colored Oak floor



Clear Seal on top of Oak floor and kitchen tablet


HARDWAX OIL

HIGH QUALITY INTERIOR WOOD FINISH

HardWax offers the advantage of oil protection and classic wax treatment in one high quality blend. Good water-repellant qualities and prevention of the wood from getting dry and brittle. It can be applied on all unfinished wood and as a durable top-coat on precolored floors achieved with American Wood Oil products such as Transparent Gold, Warm Grey, color pigments, NYC Colors, SuperGreen+, or on top of Fix & Tone.

- Suitable for all types of wood, dense, hard and exotic wood
 Penetrates naturally and deeply into the wood
 Micro-porous & fills pores

- Water repellant
- Clear, translucent non coloring finish on top of color
- Very low VOC
- Traditional European finish
- Available in Matt and Satin finish



HardWax oil on top of Oak floor





20 American Wood Oil 21

APPLICATION

The wood must be dry, smooth, dust free and sanded (with grit 100-120).

STEP 1 - CHOOSE YOUR COLOR TONE



You can make unlimited colors by adding or mixing different color pigments to the base oils. The wood must be dry, smooth, dust free and sanded (with grit 100- 120).

STEP 2 - CHOOSE YOUR PROTECTION



OR



OR



APPLICATION SHEET

See page 25 for more information about the different application methods

APPLICATION	COTTON CLOTH	PAINT BRUSH	APPLICATOR	POLISHING MACHINE
Aging Powder	YES	YES	YES	YES
Fix & Tone	YES	YES	NO	YES
Transparent Gold	YES	YES	YES	YES
Warm Grey	YES	YES	YES	YES
Rainbow Color Pigments	YES	YES	NO	DEPENDS ON COLOR
Clear Seal	NO	YES	YES	YES
Hardwax	YES	YES	YES	YES
4Nature	NO	YES	YES	NO
Supergreen+	YES	YES	YES	YES

COTTON CLOTH



Mix the oil (and pigments) well before and during the application. Use a cotton cloth to add the product and use another cotton cloth to rub off the surplus oil in the direction of the grain. Work on full boards at the time, appr. 5 to 10m2. Leave the oil to be absorbed for a few minutes before rubbing off the surplus. Let the floor dry for 8 hours . (temperature at min. 16°). Area must be well ventilated.

PAINT BRUSH



Mix the oil (and pigment) well before and during the application. Use a natural bristle brush work on full boards at the time, appr. 5 to 10 m2. Leave the oil to be absorbed for a few minutes before taking off any excess and lightly brushing out/lifting off at the end of each stroke. Let the floor dry for 8 hours. (temperature at min. 16°). Area must be well ventilated.

LAMBSWOOL APPLICATOR



Mix the oil well before and during the application. Use first a natural bristle brush to work on the edges of the room. Use the lamb's wool applicator along the full length of the floor. To avoid lab marks maintain a whet edge by overlapping sections you previously ended by several cm/inch. Let the floor dry for 8 hours (temperature at min. 16°). Area must be well ventilated.

POLISHING MACHINE



Mix the oil well before and during the application. Apply the oil in an even coat with a low speed floor buffing machine using a white polishing pad. Continue in sections until the whole floor has been finished. Let the floor dry for 8 hours (temperature at min. 16°). Area must be well ventilated.

MAINTENANCE



Daily maintenance



Periodic Maintenance



Periodic Maintenance



Remove black rubber sole marks

OILED & LAQUER

Remove dust and dirt with a dust-wiper (dry duster), or with the vacuum cleaner. Step 1 – Fill a bucket with 5 litres of lukewarm water and add a splash (±30 ml) of American Wood Oil "Cleaner" Step 2 – Mop the floor with a damp floor-cloth and allow to dry.

Spray the American Wood Oil "Cleaner" on the mark to be removed. Rub the mark with a soft sponge to remove. Then mop up any remaining "Cleaner" with a cloth soaked in clean, lukewarm water.

HARDWAX

Remove dust and dirt with a dust-wiper (dry duster), or with the vacuum cleaner.

Step 1 – Fill a bucket with 5 litres of lukewarm water and add a splash (±30 ml) of American Wood Oil "Wax & Clean"

Step 2 – Mop the floor with a damp floor-cloth and allow to dry.

Spray the American Wood Oil "Wax & Clean" on the mark to be removed. Rub the mark with a soft sponge to remove. Then mop up any remaining "Wax & Clean" with a cloth soaked in clean, lukewarm water

22 American Wood Oil American Wood Oil





Crystal Cleaner are a hydrogenated crystals formula. It is an outstanding product to remove grease, grime, dirt, organic stains, tree sap and mineral deposits. It removes mold and mildew.

- Suitable for all types of wood
- For use on siding, fences, decks,....
- Cleans and rejuvinates all wood
- Fast acting
- Eco-friendly
- Biodegradable, safe for soil and plantlife

Surface preparation:

Sweep the surface with a stiff broom or use a blower to clean the area of debries. Crystal Cleaner is most effective at temperatures where the wood is not hot to touch.

<u>Application:</u>
Pour 1 to 2 cups of Crystal Cleaner into 1 US gallon of clean water and mix.

Coverage: about 400m⁴ (approx. 40m⁴). Mist the surface with a garden hose/sprayer. Sprinkle directly using a pump-up garden sprayer and apply the solution liberally. Aggitate with a stiff bristle brush for 10-15 minutes. Do not allow the solution to dry on the surface. After: Rinse thoroughly with water.



Result of Crystal Cleaner



Colorado, USA



California is based on a blend of pure Tung oil and Brazilian Rosewood Oil. It penetrates, protects and nourishes wood fibers also offering mildew protection. California is a natural oil with an invisible UV-protection shield.

3-way oil protection:

water repellant – durable – deep penetration.

- Suitable for all types of wood, dense, hard and exotic wood
- Penetrates naturally and deeply into the wood
- Fills wood pores, micro-porous
- Water repellant
- Increased UV protection against fading
- 99% UV blocking
 Gives longer life to all species of wood.
- Low Odor
- Eco-friendly, Low VOC
- Natural color

California Pigments

A special formulated pigment on natural transoxodide-based ingredients. The pigment can only be mixed with California to create your color.



Cedar Wood Tone




Driftwood Tone



Redwood Tone

28 American Wood Oil American Wood Oil 29



American Wood Oil

International Sales Office 4 Bredestraat B2000 Antwerp Belgium tel + 32 (0)3 366 24 34

fax +32 (0)3 321 62 77

e-mail: info@americanwoodoil.com website: www.americanwoodoil.com

American Wood Oil UK

UK Office 307 Goldhawk Road W12 8EU, London UK

tel +44 (0)20 8222 0000 mob +44 (0) 77 2661 0748

e-mail: uk@americanwoodoil.com website: www.americanwoodoil.com

American Wood Oil Germany

Germany Office: 14 Bellevue 22301, Hamburg Germany

tel +49 (0) 160 7112 427

e-mail: germany@americanwoodoil.com website: www.americanwoodoil.com

American Wood Oil Asia

Asian Office: -coming soon-

e-mail: asia@americanwoodoil.com website: www.americanwoodoil.com

NYC-BRUSSELS-TEL AVIV-HAMBURG-LONDON-KIEV-TALIN-BARCELONA-ZAGREB-BUDAPAST-WARSHAW-TOKYO-BAKU

PROFESSIONAL WOOD FINISHING PROTECTION AND SEALING OF INTERIOR & EXTERIOR WOOD.



American Wood Oil

Coordinating Office: 1250 Germantown Pike, Suite 300 PA 19462 -2444, Plymouth Meeting USA

tel +001 609 654 0820 fax +001 609 654 7369

e-mail: info@americanwoodoil.com website: www.americanwoodoil.com